



Number of rungs				2 x 15	2 x 18
1	A B C D	A up to approx.	in m	8,45	9,80
		B approx.	in m	6,45	7,80
		C approx.	in m	7,70	9,10
		D approx.	in m	7,45	8,80
	A B C D	A up to approx.	in m	5,25	6,05
2		B approx.	in m	3,25	4,05
		C approx.	in m	4,35	5,20
		D approx.	in m	4,20	5,00
St	Stabiliser width approx.			1,12	1,25
Product weight approx.			in kg	20,5	27,6
Width (B) approx.			in m	0,41	0,43
	Ιτ	Depth (T) approx.	in m	0,13	0,16
	L B	Length (L) approx.	in m	4,40	5,20
Α.	Aut No			120940	100074

Combi	AA	1	K	1	
/	2x15-2x18	2x15-2x18	2 x 15 – 2 x 18	2x15-2x18	2x15-2x18
Page 78	1	2	4	6	8

MONTO®

Rope-operated two-section rung ladder Robilo®

A lightweight, rope-operated aluminium rung ladder for easy height adjustment.

- + Rope-operated aluminium ladder with easy to use height adjustment system
- + Easy to use rope guided for a high functionality
- + Can be height-adjusted rung by rung
- + Sturdy guiding profiles for easier handling
- + Slip-resistant foot caps (SafetyCap)
- + Fitted with an additional stabiliser for extra stability



Sizes 2x15 + 2x18 rungs can only be used with stabiliser according to DIN EN 131-1:2015.