

STABILO[®] Professional

Multipurpose rung ladder

Lightweight, two-section professional aluminium multipurpose ladder usable as a step ladder, leaning and extension ladder with stabiliser.

- + Sturdy, rail surrounding aluminium guiding profiles for maximum stability
- + Extruded aluminium side rails with reinforced corners
- + Longlasting 32-times flanged rung/side rail connections
- + Self-locking levers (AutoSnap-System) for safe use and transport
- + Wide stabiliser for even greater stability

Н

- + Slip-resistant rungs with a depth of 30 mm, profiled on all sides for maximum safety
- + High-strength screwed webbing straps sown into metal clips
- + Slip-resistant foot caps and plugs (SafetyCap)

According to new standard DIN EN 131-1:2015 with longer stabiliser.





Number of rungs				2 x 9	2 x 12
	ABCD	A up to approx.	in m	5,25	6,85
1		B approx.	in m	3,25	4,85
		C approx.	in m	4,35	6,05
		D approx.	in m	4,20	5,85
		A up to approx.	in m	3,85	4,65
		B approx.	in m	1,85	2,65
2		C approx.	in m	2,70	3,50
		D approx.	in m	2,55	3,35
		A up to approx.	in m	3,60	4,45
3		B approx.	in m	1,60	2,45
3		C approx.	in m	2,70	3,50
		D approx.	in m	2,60	3,40
St	abiliser width app	rox.	in m	0,87	0,97
Pr	oduct weight app	rox.	in kg	10,1	14,5
		Width (B) approx.	in m	0,43	0,43
	Depth (T) app		in m	0,12	0,14
	LB	Length (L) approx.	in m	2,70	3,55
Ar	tNo.			133472	133502



Accessories: Conductive foot end plugs Page 79

Bystern Page 78

Combi

AA	j/j	J.	K	H	Sty.	
2x9-2x12						
1	2	3	4	5	6	8