



Single-section leaning step ladder




The universally applicable heavy-duty single-sided ladder made of aluminium with steps for comfortable and safe standing as well as TRBS 2121-2-compliant use.

- + Heavy-duty single-sided step ladder for extreme use up to max. 225 kg
- + Safe application due to integrated slip-off/wall protector
- + Large-dimensioned extruded aluminium side rails with reinforced corners for a maximum of stability and a long lifetime
- + High-strength flanged step/side rail connections
- + Profiled, reinforced D-steps, 80 mm deep, for safe ascent and comfortable standing, meet the requirements of TRBS 2121-2 for the use of steps as a workplace
- + Slip-resistant foot plugs (SafetyCap)
- + Additional corner bracing up to 10 steps for maximum stability, even with high loads
- + From 12 steps and above fitted with an extra stabiliser for even greater safety

















Number of steps			6	7	8	10	12	15
1 A B	A up to approx.	m	2.70	2.90	3.15	3.60	4.10	4.80
	B approx.	m	0.70	0.90	1.15	1.60	2.10	2.80
2 6 0	C approx.	m	1.70	1.95	2.20	2.70	3.20	3.95
	D approx.	m	1.60	1.80	2.05	2.50	3.00	3.70
Product weight approx.		kg	4.3	4.9	5.5	6.7	8.5	10.3
Stabiliser width approx.		m	-	-	-	-	0.85	0.85
T B	Width (B) approx.	m	0.40	0.40	0.40	0.40	0.40	0.40
	Depth (T) approx.	m	0.10	0.10	0.10	0.10	0.10	0.10
	Length (L) approx.	m	1.70	1.95	2.20	2.70	3.20	3.95
ArtNo.			135360	135377	135384	135407	135421	135452
Combi	11	L		~	H	•	4, 4	

4

6-15

Page 96


6-10


3


12-15

6-15

8







Sizes 12–15 steps can only be used with stabiliser according to DIN EN 131-1:2015.