

Telescopic single-sided step ladder

The robust, single-sided aluminium telescopic step ladder with four rail extensions for the professional use on stairs, landings, platforms and similar height differences.

- + Four steplessly adjustable rail extensions with stable sliding guide enable use on stairs and similar height differences
- + Anodised rail extensions ensure smooth operation
- + External sliding mechanism with an infinitely variable adjustment range of up to 1,150 mm on the support section enables the greatest possible flexibility
- + High safety top rail with screwed-on tool tray for small parts and tools incl. integrated bucket hook and cable holder
- + Sturdy, rail-surrounding, screwed-on hightech metal hinge connection
- + Integrated jam protection in the hinge area provided through safety rail end plugs
- + Sturdy aluminium safety platform with slip-resistant surface and platform lifters on both sides
- + Weather resistant screwed-on webbing straps sown into metal
- + Profiled, reinforced D-steps, 80 mm deep, for safe ascent and comfortable standing, meet the requirements of TRBS 2121-2 for the use of steps as a workplace
- + High-strength flanged step/side rail connections
- + Two-component foot plugs (SafetyCap) on the rails and rail extensions for a safe stand
- + Additional corner bracing at the lowest step for maximum stability



© 2024 by KRAUSE-Werk



Number of steps			4	5	6	7
1	A up to approx.	m	2.95	3.20	3.40	3.65
	B approx.	m	0.95	1.20	1.40	1.65
2	C approx.	m	1.70	1.95	2.20	2.45
	D approx.	m	1.60	1.80	2.05	2.30
3	E approx.	mm	810	1,090	1,090	1,150
	F approx.	mm	880	1,030	1,180	1,340
	G approx.	mm	1,100	1,320	1,480	1,650
Product weight approx.		kg	6.4	7.3	8.4	9.5
Width (B) approx.		m	0.50	0.55	0.60	0.60
Depth (T) approx.		m	0.20	0.20	0.20	0.20
Length (L) approx.		m	1.75	2.00	2.25	2.50
Art.-No.			134929	134936	134943	134950

